图号：	A	
料号：	B	

Special characteristics symbol description (the symbols marked with special characteristics in the diagram must focus on control)
1. With "★" sign (indicating the key special features of the product and safety / laws and regulations)
2. With "▲" sign (important special characteristics related to the use of the client)
3. With "◆" sign (our internal special features customized according to risk assessment and impact level)特殊特性符号说明（图中标有特殊特性的符号必须重点管控）
1.带"★"号（表示产品与安全/法律法规的关键特殊特性）
2.带"▲"号（客户端使用有关的重要特殊特性）
3.带"◆"号（我司内部根据风险评估及影响程度自定义的特殊特性）

本图中提供的信息来自深圳市硕凌电子科技有限公司并且是保密的。本文包含的知识产权及其它权利仅由硕凌或其附属公司拥有。未经深圳市硕凌电子科技有限公司意，不得向任何个人、企业或团体披露。深圳市硕凌电子科技有限公司可以自行决定、制执行其知识产权;不履行或延迟行使这些权利并不构成对这些权利的放弃。
The information provided in this figure is from Shenzhen SOULIN Electronic Technology Co., Ltd. and is confidential. The intellectual property rights and other rights contained herein are owned only by shuoling or its subsidiaries. Without the consent of Shenzhen SOULIN Electronic Technology Co., Ltd., it shall not be disclosed to any individual, enterprise or group. Shenzhen SOULIN Electronic Technology Co., Ltd. can decide The enforcement of its intellectual property rights; Failure to perform or delay in exercising these rights does not constitute a waiver of these rights.

PIN数	2Pin	3Pin	4Pin
图形			

Recommended Panel Cut-out













Engagement force	≤30N	Rated volage	60V
Disengagement force	≥5N	Rated current	1A
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ
IP rating	IP67/IP68	Contact resistance	≤10mΩ
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C

	PARTS	MATERIALS	TREATMENT	AMOUNT
A	HOUSING	PA66+GF	SPECIFY COLOR	1
B	CONTACT	BRONZE	GOLD PLATED	2~4
C	OUTER CONTACT	BRASS	NICKL PLATED	1
D	NUT	BRASS	NICKL PLATED	1
E	O-RING	EPDM	BLACK	2
F				

Unless otherwise specified, tolerances are as per the table below:除非有说明，否则公差按下表：

Dimensions 尺寸标注	Tolerances公差	
	Lengths长度	Angles角度
X.	±0.30	±2°
.X	±0.25	±1.5°
.XX	±0.20	±1.0°
.XXX	±0.15	±0.5°

Design 设计	韩 信/Hanxin
Audits 审核	李雪丰/LIxuefeng
批准	游 川/Youchuan

深圳市硕凌电子科技有限公司
SHENZHEN SOULIN ELECTRONICS TECHNOLOGY CO.,LTD.

Product Model 产品型号	M5 Waterproof 2~4Pin Cable End Female Connector, Rear Lock Panel Mount M5 SW7T
Material Codes 物料编码	
Customer model, material number客户型号 物料	
Versions 版 本	A/0
Examples 比 例	1:1
Unit 单 位	MM
Figure 图 幅	A4
Third-angle projection 第 三 角 度 投 影	
Sheet 1 of 1 第 1 张 共 1 张	

图号：	A	
料号：	B	

Special characteristics symbol description (the symbols marked with special characteristics in the diagram must focus on control)
1. With "★" sign (indicating the key special features of the product and safety / laws and regulations)
2. With "▲" sign (important special characteristics related to the use of the client)
3. With "◆" sign (our internal special features customized according to risk assessment and impact level)特殊特性符号说明（图中标有特殊特性的符号必须重点管控）
1.带"★"号（表示产品与安全/法律法规的关键特殊特性）
2.带"▲"号（客户端使用有关的重要特殊特性）
3.带"◆"号（我司内部根据风险评估及影响程度自定义的特殊特性）

本图中提供的信息来自深圳市硕凌电子科技有限公司并且是保密的。本文包含的知识产权及其它权利仅由硕凌或其附属公司拥有。未经深圳市硕凌电子科技有限公司意，不得向任何个人、企业或团体披露。深圳市硕凌电子科技有限公司可以自行决定、制执行其知识产权;不履行或延迟行使这些权利并不构成对这些权利的放弃。
The information provided in this figure is from Shenzhen SOULIN Electronic Technology Co., Ltd. and is confidential. The intellectual property rights and other rights contained herein are owned only by shuoling or its subsidiaries. Without the consent of Shenzhen SOULIN Electronic Technology Co., Ltd., it shall not be disclosed to any individual, enterprise or group. Shenzhen SOULIN Electronic Technology Co., Ltd. can decide The enforcement of its intellectual property rights; Failure to perform or delay in exercising these rights does not constitute a waiver of these rights.

PIN数	2Pin	3Pin	4Pin
图形			

Recommended Panel Cut-out















Engagement force	≤30N	Rated volage	60V
Disengagement force	≥5N	Rated current	1A
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ
IP rating	IP67/IP68	Contact resistance	≤10mΩ
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C

	PARTS	MATERIALS	TREATMENT	AMOUNT
A	HOUSING	PA66+GF	SPECIFY COLOR	1
B	CONTACT	BRONZE	GOLD PLATED	2~4
C	OUTER CONTACT	BRASS	NICKL PLATED	1
D	NUT	BRASS	NICKL PLATED	1
E	O-RING	EPDM	BLACK	2
F				

Unless otherwise specified, tolerances are as per the table below:除非另有说明，否则公差按下表：

Dimensions 尺寸标注	Tolerances公差 Lengths长度	Angles角度
X.	±0.30	±2°
.X	±0.25	±1.5°
.XX	±0.20	±1.0°
.XXX	±0.15	±0.5°

Design 设计	韩 信/Hanxin						
Audits 审核	李雪丰/LIxuefeng	Versions 版 本	A/0	Examples 比 例	1:1	Unit 单 位	MM	Figure 图 幅	A4
批准	游 川/Youchuan	Third-angle projection 第 三 角 度 投 影				Sheet 1 of 1 第 1 张 共 1 张			

深圳市硕凌电子科技有限公司
SHENZHEN SOULIN ELECTRONICS TECHNOLOGY CO.,LTD.

Product Model 产品型号	M5 Waterproof 2~4Pin Cable End Female Connector, Front Lock Panel Mount M7 SW9T
Material Codes 物料编码	
Customer model, material number客户型号 物料	